FIG. 1

Y3X0   Y2X0   Y1X0   Y0X0

Y3X1   (+)←Y2X1(+)←Y1X1(+)←Y0X1

29

(Y3X3)   (+)←Y2X2(+)←Y1X2(+)←Y0X2

Y3X3   (+)←Y2X3(+)←Y1X3(+)←Y0X3

0×0

(Y*X)7 (Y*X)6 (Y*X)5 (Y*X)4 (Y*X)3 (Y*X)2 (Y*X)1 (Y*X)0

FIG. 2A

Yi Xj

29～(YiXj)

$(0 \leqq i, j \leqq 3)$

FIG. 2B

IN1

(+)←IN2=EX-OR

OUT

FIG. 2C

FIG. 3A

FIG. 3B

FIG. 3C

FIG. 3D

FIG. 5

FIG. 4

FIG. 6

FIG. 7

FIG.8

FIG. 9A

FIG. 9B

FIG. 10

FIG. 11

FIG. 12

FIG. 13

FIG. 14

FIG.15

FIG.16

REQUIRED NUMBER OF CLOCKS FOR COMMAND

| COMMAND		m=160	m=1024
ADDITION		14	68
MULTIPLY		64	2,116
SQUARE		25	133
DIVIDE	PRE-CALCULATION	35	35
	MAIN BODY	134	2,564

FIG. 17

REQUIRED NUMBER OF CLOCKS FOR GF(2^{160})

ARITHMETIC OPERATION	NUMBER OF CLOCKS	SR RATIO
ADDITION	14	ABOUT 4.6 TIMES
MULTIPLY	198	ABOUT 1.2 TIMES
SQUARE	159	ABOUT 1 TIMES

(SR RATIO)=(NUMBER OF CLOCKS)/
(NUMBER OF CLOCKS IN SHIFT REGISTER CIRCUIT)

FIG. 18

CIRCUIT SIZE (NUMBER OF GATES) OF COPROCESSOR

ARITHMETIC UNIT	8k
CONTROLLER	12.8k
RAM	8.5k
I/F	0.5k
WHOLE	ABOUT 30k

FIG. 19

ADDITIONAL CIRCUIT SIZE (NUMBER OF GATES)
FOR INTEGER BASED COPROCESSOR

ARITHMETIC UNIT	1k
CONTROLLER	3.8k
RAM	0(SHARED)
I/F	0(SHARED)
WHOLE	4.8k

FIG. 20

INDEPENDENT CIRCUIT SIZE (NUMBER OF GATES) OF GF (2^m)

|	m=160	m=1024
ARITHMETIC UNIT	3.1k	3.1k
CONTROLLER	3.8k	3.8k
RAM	2.3k	8.5k
I/F	0.5k	0.5k
WHOLE	ABOUT 10k	ABOUT 16k

FIG. 21

FIG. 23

FIG.22

FIG.24

FIG.25

GALOIS FIELD MULTIPLIER CIRCUIT

81

C0 Cm-3 Cm-2 Cm-1

A0 Am-2 Am-1

Bm-1 Bm-2 --- B0

FIG.26

90

DIVIDEND
POLYNOMIAL

RESIDUE POLYNOMIAL

92_1 92_2 $92m$ QUOTIENT
POLYNOMIAL

91_1 91_2 91_3 $91m$

f0 f1 f2 fm-1

93_1 93_2 93_3 $93m$

FIG.27